

## MID Standard Double Trunnion with Kuka Motors (other servo motors can be used)

CLASS	MODEL #	EXCHANGE AXIS MOTOR	EXCHANGE AXIS AMPLIFIER	TRUNNION AXIS MOTORS	TRUNNION AXIS DUAL AMPLIFIER	EXCHANGE 180° INDEX TIME	TRUNNION 180° INDEX TIME	EACH TRUNNION PAYLOAD	MAX TRUNNION ENVELOPE	MAX TRUNNION INERTIA	TRUNNION CENTER- LINE TO FLOOR DISTANCE	DISTANCE BETWEEN FACE PLATES
300	TMF3000- TR300-185- 750-2000-X	MG360	KSD64	MG180	KSD48	5	2	1818	1400	620	750	2000
	TMF3000- TR300-185- 750-2500-X	MG360	KSD64	MG180	KSD48	5	2	1818	1400	620	750	2500
	TMF3000- TR300-185- 750-3000-X	MG360	KSD64	MG180	KSD48	5	2	1818	1400	620	750	3000
	TMF3000- TR300-185- 900-2000-X	MG360	KSD64	MG180	KSD48	5	2	1818	1400	620	900	2000
	TMF3000- TR300-185- 900-2500-X	MG360	KSD64	MG180	KSD48	5	2	1818	1400	620	900	2500
	TMF3000- TR300-185- 900-3000-X	MG360	KSD64	MG180	KSD48	5	2	1818	1400	620	900	3000